






<b>DESCRIPTION</b>			
Total thickness	ISO 24346 (EN 428)	mm	2
Weight	ISO 23997 (EN 430)	g/m <sup>2</sup>	2995
Width of sheet	ISO 24341 (EN 426)	cm	200
Length of sheet	ISO 24341 (EN 426)	lm	20
<b>CLASSIFICATION</b>			
Norm / Product specification	-	-	ISO 10581(EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	Bfl-s1
Static electrical propensity	EN 1815	KV	<2
Electrical resistance	EN 1081	Ω	10 <sup>9</sup> -10 <sup>10</sup>
Slip resistance dry	EN 13893	-	≥0.3
Slip resistance wet	DIN 51130	class	R9
<b>PERFORMANCES</b>			
Type binder content	ISO 10581	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4
Residual indentation	ISO 24343-1 (EN 433)	mm	0.04
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	class	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>(1)</sup>	JIS Z 2801		>99% Inhibits growth
Surface treatment	-	-	EASYCARE™
Color number	-	-	16
<b>ENVIRONMENT / INDOOR AIR QUALITY</b>			
TVOC after 28 days	ISO 16000 - 6	µg/m <sup>3</sup>	<10
Certification	-	-	Floorscore®
<b>CE MARKING</b>			
	EN 14041	   	

(1) The implementation of an effective cleaning regime is the most important defence against infections.